









	MODEL	F7BCB6			F7BAB6			F7BBB5		
	ENGINE	F9Q 760			F4R 720			F9Q 762		
	TYRES	205/65 R16								
	MAXIMUM AXLE LOAD	FA = 1550    RA = 1650								
	perm. towed laden weight	4940			4925			4940		
		FA	RA	TOTAL	FA	RA	TOTAL	FA	RA	TOTAL
REFER TO NOTE 1	unladen weight MIN	1067	661	1728	1052	660	1712	1067	661	1728
	unladen weight MAX	1188	781	1969	1172	779	1951	1188	781	1969
	ALD 1 MIN	1353	1587	2940	1338	1587	2925	1353	1587	2940
	ALD 1 MAX	1424	1516	2940	1409	1516	2925	1424	1516	2940
	ALD 3 MAX	1497	1443	2940	1481	1444	2925	1497	1443	2940

Note 1:

- All weight details are based on the standard specification
- Tyres in accordance with table
- Fuel tank
- Tool kit
- Unladen weight min. : operational unladen weight (oil, water etc. filled) of model without option, without driver
- Unladen weight max. : operational unladen weight (oil, water etc. filled) of model with all options, without driver
- ALD1 min.: axle load distribution with 1 driver + max. load (design: unladen weight min.)
- ALD1 max.: axle load distribution with 1 driver + max. load (design: unladen weight max.)
- ALD3 max.: axle load distribution with 1 driver + 2 front passengers + max. load (design: unladen weight max.)

Note 2:

- Weight distribution of vehicle passengers:

	FA	RA	TOTAL
Weight of driver	53	22	75
Weight of 2 front passengers	103	47	150

Note 3:

- Minimum front axle load at perm. total weight : 1300 kg.
- Note maximum perm. axle loads: 2940 kg: FA = 1550 kg RA = 1650 kg.

Note 5:

- Vehicle variants:
- Individual front passenger seat instead of bench seat.
- Co-driver airbag
- Additional battery
- Air conditioning system.
- Trailer towing hitch.
- Loading floor and interior wood panelling.
- Continuous bulkhead with / without window.
- Fully glazed.
- 2<sup>nd</sup> side door with / without window.
- Tyre optional 215/65 R16

return to  
model overview